

Europäisches **Patentamt**

European **Patent Office** Office européen des brevets

PCT/GB04/02956

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application conformes à la version described on the following page, as originally filed.

Les documents fixés à cette attestation sont initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patent application No. Demande de brevet nº Patentanmeldung Nr.

03358010.1

REC'D 23 NOV 2004

PCT

WIPO.

Der Präsident des Europäischen Patentamts; Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets p.o.

R C van Dijk

PRIORITY

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY



Anmeldung Nr:

Application no.: 03358010.1

Demande no:

Anmeldetag:

Date of filing: 11.07.03

Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

BP Lavéra SNC
Parc Saint-Christophe,
Bâtiment Newton 1,
10 avenue de l'Entreprise
95866 Cergy Pontoise Cedex
FRANCE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention: (Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung. If no title is shown please refer to the description.
Si aucun titre n'est indiqué se referer à la description.)

Process for the (co-)polymerisation of ethylene in the gas phase

In Anspruch genommene Prioriät(en) / Priority(ies) claimed /Priorité(s) revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/Classification internationale des brevets:

C08F10/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL PT RO SE SI SK TR LI

Case 10059/B443(1)

PROCESS FOR THE (CO-)POLYMERISATION OF ETHYLENE IN THE **GAS PHASE**

The present invention relates to a process for improving the start up of polymerization or copolymerization of ethylene in a gas phase reactor, preferably a fluidised bed gas phase reactor.

- Processes for the (co)-polymerisation of olefins in the gas phase are well known in 5 the art. Such processes can be conducted for example by introducing the gaseous monomer and comonomer into a stirred and/or gas fluidised bed comprising polyolefin and a catalyst for the polymerisation.
- 10 In the gas fluidised bed polymerisation of olefins, the polymerisation is conducted in a fluidised bed reactor wherein a bed of polymer particles is maintained in a fluidised state by means of an ascending gas stream comprising the gaseous reaction monomer. The start-up of such a polymerisation generally employs a bed of polymer particles similar to the polymer, which it is desired to manufacture.
- 15 During the course of polymerisation, fresh polymer is generated by the catalytic polymerisation of the monomer, and polymer product is withdrawn to maintain the bed at more or less constant volume. An industrially favoured process employs a fluidisation grid to distribute the fluidising gas to the bed, and to act as a support for the bed when the supply of gas is cut off. The polymer produced is
- 20 generally withdrawn from the reactor via a discharge conduit arranged in the

lower portion of the reactor, near the fluidisation grid. The fluidised bed consists in a bed of growing polymer particles. This bed is maintained in a fluidised condition by the continuous upward flow from the base of the reactor of a fluidising gas.

5

10

15

20

The polymerisation of olefins is an exothermic reaction and it is therefore necessary to provide means to cool the bed to remove the heat of polymerisation. In the absence of such cooling the bed would increase in temperature and, for example, the catalyst becomes inactive or the bed commences to fuse. In the fluidised bed polymerisation of olefins, the preferred method for removing the heat of polymerisation is by supplying to the polymerisation reactor a gas, the fluidising gas, which is at a temperature lower than the desired polymerisation temperature, passing the gas through the fluidised bed to conduct away the heat of polymerisation, removing the gas from the reactor and cooling it by passage through an external heat exchanger, and recycling it to the bed. The temperature of the recycle gas can be adjusted in the heat exchanger to maintain the fluidised bed at the desired polymerisation temperature. In this method of polymerising alpha olefins, the recycle gas generally comprises the monomer and comonomer olefins, optionally together with, for example, an inert diluent gas such as nitrogen or a gaseous chain transfer agent such as hydrogen. Thus, the recycle gas serves to supply the monomer to the bed, to fluidise the bed, and to maintain the bed at the desired temperature. Monomers consumed by the polymerisation reaction are normally replaced by adding make up gas or liquid to the polymerisation zone or reaction loop.

25

30

It has now been found an improved start-up operation wherein the polymerization or copolymerisation reaction starts immediately after the alpha-olefins have been brought into contact with the catalyst system and a charge powder, without the risk of formation of agglomerates or fine particles, the polyolefins produced during this period of start up having constant properties and having immediately the desired quality.

The object of the present invention is therefore a process for the polymerisation or copolymerisation in the gas phase of ethylene by bringing the said ethylene into contact, under polymerization or copolymerisation conditions in a reactor in which the start-up bed is fluidised and/or agitated with mechanical stirring, with a catalyst system, which process comprises a pre start-up operation characterized in that, prior to the introduction of the catalytic system in the reactor, it comprises the following steps

- 1. determining the density d and melt index MI of the polyethylene powder to be produced at start-up,
- 10 2. heating the start-up bed by controlling the temperature inside the reactor such that
 - a. the temperature is maintained at least 0.5°C below the sintering temperature of the start-up bed, and
 - b. the temperature is maintained at a value equal or higher than the one corresponding to a RTSE value of 4.4 for the d and MI values of the polyethylene powder to be produced.

It is also an object of the present invention to provide with a continuous gas fluidized bed process for the polymerization of ethylene monomer and one or more optional alpha-olefins, in a fluidized bed reactor by continuously recycling a gaseous stream comprising at least some of the ethylene through the fluidized bed, comprising the steps of

- 1. having and/or introducing a seed bed into the reactor,
- 2. some or all of the recycling gas acting as the fluidizing gas through the bed in order to maintain the bed in the fluidized state.
- 3. heating the fluidizing gas with an external heating system,
- 4. determining the density d and melt index MI of the polyethylene powder to be produced at start-up
- 5. identifying in the RTSE tables the temperatures corresponding to a RTSE value of 4.4 for the polyethylene powder to be produced at start-up,
- 6. having and/or building into the reactor the appropriate reactive olefin gas and/or liquid environment, and

25

20

5

15

- a final step of introducing into the reactor the active polymerization catalyst specie which instantaneously starts the olefin polymerization process,
- 3. characterized in that, before the final step of introducing the catalyst into the reactor, the heating step is conducted by controlling the temperature inside the reactor such that

5

10

- a. the temperature is maintained at least 0.5°C below the sintering temperature of the start-up bed, and
- b. the temperature is maintained at a value equal or higher than the one identified in above step 5 (i.e. the temperature corresponding to a RTSE value of 4.4 for the d and MI values of the polyethylene powder to be produced).
- According to a preferred embodiment of the present invention, the heating step of the start-up bed by controlling the temperature inside the reactor is also such that the temperature is maintained at a value equal or lower than the one corresponding to a RTSE value of 4.2 for the d and MI values of the polyethylene powder to be produced.
- The densities can be measured according to ASTM-D-792 and defined as in ASTM-D-1248-84. The melt index can be measured according to ASTM-D-1238, condition A (2.16kg).
- Figures 1 to 12 represent the RTSE tables covering the polyethylene grades to be produced according to the present invention.
 - The RTSE value is indicated in the attached tables (figure 1 to 12) which cover polyethylene grades having a density from 915 to 960 and a melt index from 0.5 to 30. To each density/melt index couple corresponds a 4.2 and 4.4 RTSE value and a corresponding temperature as indicated in the tables. For density or melt index values that are falling at the border of operating envelopes (window), the corresponding operating temperature envelope can easily be calculated by making linear interpolations.

For example, in figure 6, for a 940/4.8 density /melt index couple, the temperature at an RTSE of 4.4 is 100.2°C and the temperature at an RTSE of 4.2 is 105.8; thus, when it is decided to produce a 940/4.8 d/MI polyethylene grade, the prestart-up heating step according to the present invention should be performed at a temperature which is at least equal to 100.2°C (RTSE=4.4) and, preferably, lower than (or equal to) 105.8°C (RTSE=4.2).

For a 940/5.05 d/MI polyethylene grade, the calculation gives

T°C	RTSE=4.4	RTSE=4.2
940/4.8	100.2	105.8
940/5.3	99.5	105.1
→ 940/5.05	(100.2+99.5)/2	(105.8+105.1)/2

5

i.e., a pre-start-up heating step according to the present invention which should be performed at a temperature which is at least equal to 99.85°C (RTSE=4.4) and, preferably, lower than (or equal to) 105.45°C (RTSE=4.2).

In order to provide the most efficient pre-start-up treatment, it is important that
this treatment should last until when the catalyst is introduced. It is also preferred
that the heating is performed at least five minutes and preferably over 15 minutes
before catalyst injection.

The Applicants have unexpectedly found that this temperature control leads to smooth and improved in all aspects polymerization start-ups.

The essential feature of the present invention lies in said strict control of the reactor inside temperature during pre-start-up.

As can been seen from the attached figures, the said reactor temperatures are unusually high for gas phase operations. In the prior art start-up operations, the temperature inside the reactor remains usually very low before the catalyst is first injected. The particular feature according to the present invention lies in the heating of the reactor before start-up in order to reach the appropriate temperature inside the reactor before catalyst injection and start-up.

Said heating can be done by any appropriate mean, e.g. by using a heat exchanger in the reaction loop. However, it is obvious for the man knowledgeable in the art that the usual cooling water system (that is based on an open loop) will not allow to reach the heating temperatures required according to the present invention. Therefore, according to the present invention, we preferably use a closed loop pressurised water cooling system (using steam) in order to provide reactor operating temperatures before start-up in excess of 100°C.

5

20

25

30

35

According to a preferred embodiment, the present invention is especially valuable for the polymer grade which requires a heating temperature of at least 95°C, preferably at least 100°C. For example, according to the present invention, this means that the grade to be produced at start-up has (in the attached tables) for a RTSE value of 4.4 a temperature which is at least of 95°C, preferably at least 100°C.

Said pre start-up operation may also advantageously be performed before and during the introduction of the start-up bed (charge powder) into the reactor. The charge powder used for the start up of polymerisation or copolymerisation consists of solid particles of an inorganic product, such as silica, alumina, talc or magnesia, or else an organic product such as a polymer or copolymer. In particular the charge powder may be a polyolefin powder preferably of the same nature as that of the polyolefin powder to be produced, so that as soon as the reaction starts up, polyolefin of the desired quality is obtained immediately. Such a charge powder may in particular originate from a previous polymerisation or copolymerisation reaction. In this way one may use as charge powder a powder of a polyethylene, a polypropylene, a copolymer of ethylene with less than 20% by weight of one or more other alpha-olefins comprising, for example, from 3 to 12 carbon atoms, an elastomeric copolymer of ethylene with from 30 to 70% by weight of propylene, a copolymer of ethylene with less than 20% by weight of ethylene or one or more other alpha-olefins comprising from 4 to 12 carbon atoms, or a copolymer of propylene with from 10 to 40% by weight of 1-butene or a mixture of 1-butene and ethylene. Advantageously the charge powder consists of particles having a mean diameter by mass comprised between 200 and 5000 microns, and preferably comprised between 500 and 3000 microns. The size of the

charge powder particles is chosen partly as a function of the size of the polyolefin particles to be produced, and partly as a function of the type of polymerisation reactor and conditions of use of this reactor, such as for example the speed of fluidisation which may for example be comprised between 2 to 10 times the minimum speed of fluidisation of the polyolefin particles to be produced.

5

10

15

20

25

30

According to the present invention, the completion of the mandatory heating step is done before the introduction of the active polymerization catalyst specie inside the reactor. It will be apparent for the man skilled in the art that the present invention process can also advantageously be used after a shutdown of the previous polymerization process. Consequently, there might be residual polymerization occurring when proceeding with the heating step according to the present invention. It is thus essential to continue to control the temperature according to the process claimed until the introduction of the catalyst specie into the reactor and the start-up polymerisation.

According to a preferred embodiment of the present invention, the pre-start up procedure also includes a cleaning process (pre start-up operation) characterized in that, prior to the introduction of the catalytic system in the reactor, the reactor is subjected to a cleaning treatment comprising the steps of introducing into the reactor an alkane having from 4 to 8 carbon atoms, circulating said alkane across the reactor under pressure and elevated temperature, depressurizing and purging the reactor.

The Applicants have unexpectedly found that this additional alkane treatment lead to smooth and improved in all aspects polymerization start-ups, as showed in the examples. While not wishing to be bound to this explanation, the Applicants believe that it is the absorption capacity of the alkane which positively impacts on the polymer residues and impurities present on the reactor wall, in the piping and exchangers, so that during the depressurizing/purging steps a high desorption of these residues and impurities occur by mechanical and/or dissolution and/or azeotropic type mechanisms.

The cleaning treatment consists in introducing into the reactor an alkane having from 4 to 8 carbon atoms, circulating said alkane across the reactor under pressure, depressurizing and purging the reactor.

5

10

15

35

The introduction of the alkane in a fluidised bed and/or with mechanical stirring, is preferably performed in the presence of an inert gas. In particular the treatment may be performed in the presence of nitrogen. It is also preferably performed under airtight conditions in order to avoid any oxygen ingress. It is also preferably performed in the absence of reacting gas like the olefins.

For the purpose of the present description and appended claims, "under pressure" treatment means that the pressure inside the reactor is at least above the atmospheric pressure. The alkane cleaning treatment is preferably carried out under a pressure comprised between 5 and 30 bars. For the purpose of the present description and appended claims, a treatment at an "elevated temperature" means that the treatment is performed at a reactor temperature of at least 40°C, preferably performed at a temperature comprised between 50 and 120°C and more preferably at a temperature comprised between 70 and 110°C. Preferably, when a charge powder is present, the treatment temperature should be below the temperature at which the particles of charge powder begin to soften and form agglomerates.

The alkane is for example, butane, pentane, hexane, heptane or octane. Pentane is preferably used.

The quantity of alkane used according to the invention depends on the state of purity of both the reactor loop and the charge powder. Preferably, the quantity of 20 alkane used for the treatment is such that the alkane partial pressure is comprised between 25 and 95% of the saturated vapor pressure of the said alkane under the treatment conditions (temperature and pressure). More preferably, the quantity of alkane used for the treatment is such that the alkane partial pressure is comprised 25 between 45 and 75% of the saturated vapor pressure of the said alkane under the treatment conditions (temperature and pressure). In order to provide the most efficient cleaning treatment, it is important that this treatment should last at least five minutes and preferably over 15 minutes. As already indicated, the cleaning process includes after the alkane circulation 30 under pressure a depressurizing step. Then, the consecutive purge operation(s) is/are performed according to techniques in themselves known, such as successive operations of pressurising and degassing the reactor by means of gases or a mixture of gases as referred to above. They may be carried out under a pressure at least equal to atmospheric pressure, preferably under a pressure comprised

between 0.1 and 5 MPa, at a temperature equal to or greater than 0 DEG C., but

less than the temperature at which the charge powder particles begin to soften and form agglomerates, and preferably at a temperature comprised between 40 DEG and 120 DEG C.

Any appropriate additional cleaning treatment may also be performed. For example, the reactor may additionally be treated with an organoaluminium compound of the formula AlRn X3-n in which R is an alkyl group comprising from 2 to 12 carbon atoms, X is a hydrogen or halogen atom, or an alcoholate group, and n is a whole number or fraction comprised between 1 and 3. Said organoaluminium additional treatment, if used, is preferably performed after the alkane treatment.

The organoaluminium compound, when used, may be chosen from amongst the trialkylaluminium compounds or hydrides, chlorides or alcoholates of alkylaluminium. Generally it is preferred to use a trialkylaluminium such as triethylaluminium, trisobutylaluminium, tri-n-hexyl-aluminium or tri-n-octyl aluminium. In certain cases, especially with a view to simplifying the process of the invention, the organoaluminium compound may advantageouly be of the same nature as that used as co-catalyst associated with the catalyst in the catalyst system.

20

25

15

Another additional treatment could be a dehydration treatment, which essentially consists in purge operations. If used, said additional dehydration treatment is advantageously performed before the alkane cleaning treatment of the present invention.

According to a preferred embodiment of the present invention, the cleaning treatments (purges, organoaluminum compounds and alkanes) are performed before composing the reacting gas phase. Then, contacting the olefins with the charge powder in the presence of the catalytic system may be performed in a manner in itself known, by means of a polymerisation or copolymerisation reactor with a fluidized bed and/or with mechanical stirring. The reactor is fed with a reaction gas mixture consisting of 1 or more (alpha)-olefins and optionally hydrogen and/or one or more inert gases (including additional optional alkanes), under the appropriate conditions of the polymerisation or copolymerisation reaction in the gas phase.

35

Surprisingly, it has been observed that when one wishes to attain in an advantageous manner, in a relatively short time, a stable production of polyolefin of the desired quality, it is possible thanks to the process of the invention to perform the initial stage of the polymerisation or copolymerisation in the presence of the catalytic system in a relatively large quantities, without forming agglomerates or fine particles.

5

10

The process according to the present invention is particularly suitable for the manufacture of copolymers of ethylene. Preferred alpha-olefins used in combination with ethylene in the process of the present invention are those having from 4 to 8 carbon atoms. The preferred alpha-olefins are but-l-ene, pent-l-ene, hex-l-ene, 4-methylpent-l-ene, oct-l-ene and butadiene, the most preferred comonomer being the hex-l-ene.

- When liquid condenses out of the recycle gaseous stream, it can be a condensable monomer, e.g. but-1-ene, hex-1-ene, 4-methylpent-1-ene or octene used as a comonomer, and/or an optional inert condensable liquid, e.g. inert hydrocarbon(s), such as C4-C8 alkane(s) or cycloalkane(s), particularly butane, pentane or hexane.
- The process is particularly suitable for polymerising olefins at an absolute pressure of between 0.5 and 6 MPa and at a temperature of between 55 and 135°C, preferably 80°C and 120°C.
- The polymerisation is preferably carried out continuously in a vertical fluidised bed reactor according to techniques known in themselves and in equipment such as that described in European patent application EP-0 855 411, French Patent No. 2,207,145 or French Patent No. 2,335,526. The process of the invention is particularly well suited to industrial-scale reactors of very large size.
- 30 The polymerisation reaction may be carried out in the presence of a catalyst system of the Ziegler-Natta type, consisting of a solid catalyst essentially comprising a compound of a transition metal and of a cocatalyst comprising an

organic compound of a metal (i.e. an organometallic compound, for example an alkylaluminium compound). High-activity catalyst systems have already been known for a number of years and are capable of producing large quantities of polymer in a relatively short time, and thus make it possible to avoid a step of removing catalyst residues from the polymer. These high-activity catalyst 5 systems generally comprise a solid catalyst consisting essentially of atoms of transition metal, of magnesium and of halogen. The process is also suitable for use with Ziegler catalysts supported on silica. The process is also especially suitable for use with metallocene catalysts in view of the particular affinity and reactivity experienced with comonomers and hydrogen. The process can also be 10 advantageously applied with a late transition metal catalyst, i.e. a metal from Groups VIIIb or Ib (Groups 8-11) of the Periodic Table. In particular the metals Fe, Co, Ni, Ru, Rh, Pd, Os, Ir, and Pt are preferred, especially Fe, Co and Ni. The late transition metal complex may comprise bidentate or tridentate ligands, preferably coordinated to the metal through nitrogen atoms. As examples are those 15 complexes disclosed in WO96/23010. Suitable iron and/or cobalt complexes catalysts can also be found in WO98/27124 or in WO99/12981. It is also possible to use a high-activity catalyst consisting essentially of a chromium oxide activated by a heat treatment and associated with a granular 20 support based on a refractory oxide. The catalyst may suitably be employed in the form of a prepolymer powder prepared beforehand during a prepolymerisation stage with the aid of a catalyst as described above. The prepolymerisation may be carried out by any suitable process, for example, polymerisation in a liquid hydrocarbon diluent or in the gas 25 phase using a batch process, a semi-continuous process or a continuous process. According to a preferred embodiment of the present invention, the catalyst is a Ziegler-Natta catalyst (i.e., non-metallocene) containing magnesium and titanium; the magnesium is preferably acting as the support; the catalyst is thus preferably non supported on silica. Preferably, the catalyst is subjected to a 30 prepolymerisation stage. A most preferred catalyst corresponds to the catalysts disclosed in WO9324542.

According to a preferred embodiment of the present invention, the polyethylene has a density comprised between 915 and 960 kg/m3 and a melt index comprised between 0.5 and 30.

5 **CLAIMS**

- Process for the polymerisation or copolymerisation in the gas phase of ethylene by bringing the said ethylene into contact, under polymerization or copolymerisation conditions in a reactor in which the start-up bed is fluidised and/or agitated with mechanical stirring, with a catalyst system, which process comprises a pre start-up operation characterized in that, prior to the introduction of the catalytic system in the reactor, it comprises the following steps
- 15 1. determining the density d and melt index MI of the polyethylene powder to be produced at start-up,
 - 2. heating the start-up bed by controlling the temperature inside the reactor such that
 - a. the temperature is maintained at least 0.5°C below the sintering temperature of the start-up bed, and
 - b. the temperature is maintained at a value equal or higher than the one corresponding to a RTSE value of 4.4 for the d and MI values of the polyethylene powder to be produced.
- 25 2. Continuous gas fluidized bed process for the polymerization of ethylene monomer and one or more optional alpha-olefins, in a fluidized bed reactor by continuously recycling a gaseous stream comprising at least some of the ethylene through the fluidized bed, comprising the steps of
 - 1. having and/or introducing a seed bed into the reactor,
- 2. some or all of the recycling gas acting as the fluidizing gas through the bed in order to maintain the bed in the fluidized state,
 - 3. heating the fluidizing gas with an external heating system,
 - 4. determining the density d and melt index MI of the polyethylene powder to be produced at start-up

- 5. identifying in the RTSE tables the temperature corresponding to a RTSE value of 4.4 for the polyethylene powder to be produced at start-up,
- 6. having and/or building into the reactor the appropriate reactive olefin gas and/or liquid environment, and
- a final step of introducing into the reactor the active polymerization catalyst specie which instantaneously starts the olefin polymerization process,

5

15

characterized in that, before the final step of introducing the catalyst into the reactor, the heating step is conducted by controlling the temperature inside the reactor such that

- a. the temperature is maintained at least 0.5°C below the sintering temperature of the start-up bed, and
- b. the temperature is maintained at a value equal or higher than the one identified in above step 5 (i.e. the temperature corresponding to a RTSE value of 4.4 for the d and MI values of the polyethylene powder to be produced).
- 3. Process according to claim 1 or 2 wherein the heating step of the start-up bed by controlling the temperature inside the reactor is also such that the temperature is maintained at a value equal or lower than the one corresponding to a RTSE value of 4.2 for the d and MI values of the polyethylene powder to be produced.
- 4. Process according to any of the preceding claims wherein the polymer grade to be produced at start-up requires a heating temperature of at least 95°C, preferably at least 100°C according to its corresponding 4.2 RTSE value in the tables.

5 ABSTRACT

PROCESS FOR THE (CO-)POLYMERISATION OF ETHYLENE IN THE GAS PHASE

The present invention relates to a process for improving the start up of polymerization or copolymerization of ethylene in a gas phase reactor, preferably a fluidised bed gas phase reactor.

l	
SS	
7	
•	•
•	

			1	MEL	T-IN	DEX		•							
30,0	27,0	24,0	22,0	20,0	18,0	16,0	14,0	13,0	12,0	11,0					
THE RIGHT	ALL B	AT SE	A RIGHT	AT A A A A A A A A A A A A A A A A A A	ATTER HISE AGE	t Right	ASE ASE	RITGE 4,4 RITGE	AT SEE SEEN	お記れ	ထွ				
2 7 8 7	2 7 2 7	8 4 8 4	E 1 E 1	5 18 1	95 T	9.5	夏山岩山	18,1 18,1	10000000000000000000000000000000000000	12 7 E 7	5				
1, 35. L 1, 35. L 1, 35. L	12 mg 7 mg 7	HISE 7 4,2 98,7			4.2 101 4.2 101	42 H	12 H	RTSE 1	41 E	A SERIES	946				
to might	₽ 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				24 A 10 M	2 RR 2 RR 2 C	2 7 6 7 2 8 4 8	1° RISE 1° RISE 1° RISE 100,0 4,2	17 RTSE 104,5 4.4		_				
12 KING	947 (02) 11 (03) 17 (10) 17 (1														
	17 1948 17 1952 17 195														
100,0 4,2 1	お記と問	お麗な調	in 2 in 3	S 2 2 2	2 開 2 開	な調な調	AND	七 图 七 图	七 覆 七 覆	2 mg 2 mg	_				
100,7 RTSg	17 RTSE 101,3 4,2	B - B - B	T RISE	2 1 S 7	夏十是十	104,7 RISE 42 4.4 42 4.4	<u> </u>	第一第一	F 및 F	三世 二世	949				
중 기용 기	三二二 连	1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		で 関 を 関	お 関 コ 関 コ	44 100,8 42 100,4	HISE T	113E T	MISE T 41. 1025 MISE T 42. 108,2	8				
1 m 1 m		なる。	FINE FINE	1 2 4 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ដង្ហីដង្ហី	105,5 T RISE		第 2 票 3	お習る習		<u>س</u> ر				
	<u> </u>	12 T	28.4 TRIBE	E 7 8 7	통 기원 기 호 및 호 및	<u> </u>	9 7 g 7	日日日	夏一夏一	8 18 1					
寛一思っ	ğ - Ş -	2 1 2 1 3 E		H 28 -1	2	2 日間 コ	日間と聞い	記り記し	RISE T 4.4 101,3 RISE T 4.2 108,9	RTSE T 4,4 103,9 RTSE T 4,2 109,5	952				
計画は			THE STATE OF			101,2 4,6 101,2 4,6 100,0 4,2		A RIE	A H A H	2 8 2	953				
7 8138 7 4.4 138 138 14.2	17 mag	를 기尺 기통 : 중 : 중 :		100,4 4.	101,1 4,4 102,7 4,4 103,7 4,4 4,2	101,0 4.4 107,5 4.2		100,4 4.4 100,6 4.4 100,6 4.4							
로 가용 가	<u> </u>				2 7 2 7	夏州夏州		2	RISE T: 4,4 104,6 RISE T: 4,2 110,2	RTSE 7	22				
RISE T 4,4 99,2 RISE T 4,2 104,9				RING A	[및 의 및 리				計算な調	調金費の	955				
17 RTSE 104,0 4,2		TOUS ASSESSED ASSESSE	T IN A RIBE	T RISE	102.4 1.4. 102.4 1.4. 102.6 1.2	103,2 4,4 103,2 4,4 108,8	194,1 4,4 194,1 4,4 196,7 4,2								
第一十十二	下資下資	5 - E - E	7 2 7	H TO ANSE		F 및 F 를			의 기 (1 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기		දු				
RTSE T	KISE T		RISE S			. 필는 필	T RISE 104,7 4,4 1 110,3 4,2 1			な 麗 本 麗	957				
		101,7 4,6 101,7 4,6 101,7 4,6 101,2 4,2	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		E T KIEE 100.0 4.4 1	A RIES	105,3 4,4 106,3 4,4 110,0		10 7 10 10 10 10 10 10 10 10 10 10 10 10 10	' 					
1 1 1 1 1 1 1 1 1 1	19 72 19 7		न हुँ न हुँ			ESTIN TO AND I	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		2 E 100,0	2	950				
1002 T		1 32 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			A HORE		A REE				959				
1 2 M	L RIGHT		T RISE	7 (S ₄ 7)		T RISE	T RISE T. RISE	T RISE	TO RUSE	* - - - - - - 					
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			7 8 7 5	7 K 7	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		19 7 19 7 19 19 19 19 19 19 19 19 19 19 19 19 19			8				

1						_							M	E	ĘĻ	٦.	_	11	1[כ	Ë	X	, · `												
٠	3	11,0			9.9			0, 1			,8 0			7,2			Ö,	7		Ş	n O			<u>၂</u>			4,8			4,3			<u>ဒ</u> ,9	1	
ı	<u>. </u>	44 887			6	1	6.	' 많	7	,6 6	, g	7	7.4	기품	7	물	TISE T	KISE	\$2 108,8	HISE T	44 1002	T IS	A SE	A JOLO	RISE 7	42 E	1,01	RISE 7	12 E	2 8	RISE T	A SE .	\$	KTSE T	945
	~ H	1	7	9 M	ig.	RISE T RISE		~	मध्य ४ सध	រស្ន	1 2	1 33	រ គ		TSE T	4,2 108,9		RISE T	4,2 100,0	ANDER 7	104.0		RISE T	\$	FUSE T FUSE	3	4,4 105,5	HISE T	A PART T	108,		3 88	2	<u>-</u>	946
į	T RINE	100 -		HISE	101,1	RIS		# B.103	T RISE	100 T	13 14	기	1000 -12	1	T Kris	100,7 4,2	104.1 4.4 104.6	7	130,2	साइट 7 साइट	101	42 111,2 42	T ATTE	66 4.	7	7	100.2	KISE T RISE		ş.	RISE T RISE	RISE T	4.4 (07.0		7.00
	KUSE	4,4 101,8	į	-1	<u> </u>	1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	4	A4 184	T RISE T	108,0 4.2 108.8 4.2	103.4.4. 104.1	T RISE T RISE	T. RTSE T	104,2 4,4 104,9 4,4	T RUSE T	110,5 4.2. 111,3	104.0 4,4 105,0 4,4	T' RISE · T'	111,2 4,2 111,0	T RISE T	7 7100	遠	T RIS	100,3	1120	7	107,0 4,4	T 17 17 17 17 17 17 17 17 17 17 17 17 17	T RISE	107,8		TRISE	108/4	1 6	0/8
in india	-	4.4 102.5 4.4	į	RISE T RISE	Wide - Nise		म्	104,1		RISE T RISE	4.4 104.9 4.4	KISE T KIS	RISE T RISE	4,4 105,0 4,4	KTSE T' RIS	42 1120 A3	4,4 100,4	KISE T KI	42		KIS	ない。	HISE T	<u>평</u> ·	1 3	ᅰ	8 -		L 3SIN	44 100,2	į	T X	109,2 4,4 109,9	g	2
108,91 4,2 100,0	344		ů	T RISE T		2	T RISE	104.6		R	105,0	7 2		108,3		197 KIR	<u>1</u>	7 28			RIS	12. 12.	RISE T RISE	108.5	1 62		100.2 A.A	12	T RIES		-12	7	ALA HOLE		
42 110,2 42		HISE T	42 111.0	FIRST TO A	स	鼍	T RISE T RISE	5 4.4 tono 4.4	11,8 42 112,0 42	HISE T RISE	3 4,4 100,9	בנות בנות בנות	म साइह म साइह	7.0 4.4 107.7	T REAL TO	T RISE T	107,8 4,4 106,4 4,4 1	T RISE T	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	100,5 4, 100,1	T RISE T RISE	12 115,		TODO AL MODE	û	T MISE T		Įį		4	à	T RISE T	T RIBE T		
110,9 4,2 111,5		HISE T	111,6 4,2	T SE	RIBE	12 22		NI N	10.2 1.2	THE SE	107.6 A.A	1 E	7 Rigg	2 - 12 A	l i	THE STATE OF	28 14.4		FIE	4.4 100.B 4.4	RISE T RISE	42 110,1 42		: 8	170g			116,9 4,2 117,0 4,2	MEE T RISE	RISE T RI	42 1182	RISE T RISE	RISE T	95 <u>4</u>	
42 1121	T RISE T	RISE T	42 1120	មន្ទឹ	RISE T	₫.	T PIET TO DIE	T HIGH	12 114	T RIBE T	į J	11 23 118	T RISE T	TOP KISE T	116.3 4.2 115.	-4	109,7 4,4 110	1 00	RISE	10,4	77 RTS2	110,6 4.2		RTS	117,4		T Rig	18,2		RIE	118.6 4.2	1 2	7	955 956	
112,7 4,2	1		136 CA	19.	٦	4,2 114,2 4,2		HISE T KISE	42 115,0 4	RISE T RISE	: 3	i ii	RISE T RISE	RISE T RISE	115,9 4,2 118,5 4	ਹ।	3 4.4 · 110.0 4	t,	RISE T	*	7	117,4 4,2 118,0	į	7	118,0 4,2 118,5	阛	7	42 119,4	ᆌ	RISE T	4,2 120,0	Ē	T RISE T	6 957	
113.3		T RISE T	HISO 42	108.4	THISE	114,9 4,2 116.3	1857	T RIS	115,8 4,2		FIRE	110,3 4,2		- A	17.11			117,8 4,2	म संद्र	1121 44		A RISE	112,8	T RISE	19 - C	113.6 4.4	RISE T RISE	42 1200 42	7 (10) T	ATTSE T		텷		958 9	
និន្	4.4 108,7	A S	T E	*	ag i	AT SEE TO	\$	3	ಭ	7 110,5 4,4 111,0	RISE	2	7 2 44 111,8	T RTEE	17,0 4,2	T RISE T		118,3 4,2	म साइट म	1127 44	7 PIEC T	RIE	10. 12	7		13.1	T RISE T	120.5 A.2	114,0	-	7 . T	tigg 44	-)59 960	

		•		MEL	T-IN	DEX					<u>.</u>
4,0	3,6	3,2	2,9	2,6	2,3	2,1	1,9	1,7	1,5	1,4	· .
								RISE T 4,4 75,8 RISE T 4,2 61,2			915
お開ま調	お開ま開	t	計算な調査		ansg ±	A RITER AND	A RISE	AUSE THE	ta Ring	4 RITER	916
\$ 2 g 2			HISE T 1 44 758 HISE T 1 42 81,1	た 麗 な 麗	RISE T 14 44 769 RISE T 11 42 825	t High	2 2 2 2	T RISE T 77,1 4,4 78,5 T RISE T 62,7 4,2 84,2	to Ring	T RISE T 78.0 4.4 79,6 T RISE T 83,7 4.2 85,1	6 917
4.4 74,6 RTSE T 4.2 80,6	4.4 78,6 RISE T 4.2 81,2	A14 70,4 RISE T 4,2 82,0	1 3813 1 3813 1 3813 1 3813	#18E T 4,4 77,6 #18E T 4,2 83,3	4,4 78,3 1 38118 4,2 .84,0	4,4 .78;6 4,2 .83;8 4,2 .84;8 4,2 .84;8	41 774 41 774 41 32 T	RTSE T B 44 80,0 RTSE T 2 42 85,0	ATSE ALS BEIR	RIBE T 4.4 80.9 RISE T	918
日本はよ	日日日日	합니콥그	いなり		RISE T RISE 44 79,9 4,4 RISE T RISE 42 85,4 4,2	2 2 2	ATSE T 4.4 80,9 RTSE T 4.2 84,5	RTSE T 4,4 B1,4 RTSE T 4,2 07,0	RISE T 4.4 82.0 RISE T 4.2 87.7	A4 824 A7 824 A2 88,0	919
	医口器口	옮겨경겨	돌겨울ㅋ	HTSE T RTSE -1,4 80,5 4,4 HTSE T RTSE -1,2 86,1 4,2	몸겨끊겨	2 7 2 7	불가문가	RISE T RISE 4.4 82.6 4.4 RISE T RISE 4.2 88.5 4.2	를 그를 그	\$ - B -	920
를 구 됐 구	79,9 4.4 78,5 7 8152 7,2 4.3	윤 - 윤 -	뚫겨混겨	2 1 2 7	器コロコ	製す品す	용 기원 기	8 7 K 7		12 808 1 8188 14 828 44 15 818 13 818	921
t	86 T 82 T	E7,6 4,6	1 RISE 82.6 4.4 1 RISE 4.2 4.2	17 RT 82 4.5 81 82 4.2	1. RIES 84,0 4,6 1. RIES 89,8 4,2	845 T RIE 841 CA	記っ語っ	2 7 8 7		12 3 1 3 1	922 9
	t i i t i		T RISE : C.,0 4,4 8 C.)6 4,2 9	12 M	T RTSE T RTSE T RTSE 51,0 4,2 8	AT THE REPORT OF THE PERSON IN	t	T RISE 67,0 4.4 12 4.2 4.2	T Mass	1	923 924
な調ま調	17 RTSE T RTSE T 82,6 4,2 80,5		T RISE T 84,4 80,6 T RISE T 90,9 4,2 82,2	A RES	た 麗 エ 麗	T RISE T 87.2 4.4 88.5 T RISE T 82.8 4.3 . 84.1	た 麗 よ 麗	お記れる	06,0 4,4 80,3 07,0 4,2 85,6 4,2 85,6	なるより	4 925
4.4 85.9 4.2 91.5	**************************************	RISE T 44 873 RISE T 42 829	1,4 67,9 1,2 63,5 1,2 63,5	RTSE T - 4,4 98,6 P - 4,2 94,2	6'98 5'9 5'08 9'9 1. 35!34	#15E T	A BER A	RISE T 8 4,4 90,9 RISE T 3 4,2 96,5	1 N 2 N	t ii t	926
記するす	문가랍기	元 世界 マ	를 가 ^및 가	용기물기	おいます。これのよう	RISE T 4,4 91,1 RISE T 4,2 94,7	RISE T 44 81,0 RISE T 42 87,2	1 2018 1 218 1 218	KISE T 4.2 92,9 4.2 98,4	RISE T 4.4 80.2 RISE T 4.2 90.8	927
第一章 コ	語コ百日	출그를 그		F 그 를 그	월 기를 기		[기] 기	급 -1 ố·-1	물 - 로 -		928
4 89,8 4,4 2 17 RISE 2 65,2 4,2		불기움기	25 T RISE 2 01.7 4.4 36 T RISE 2 07.3 4.2	7 823 7	8 7 g 7	17 17 18 18 18 18 18 18 18 18 18 18 18 18 18	調けます	12 15	ᅙᇶᆉᄙᆞᇰᅱ	·	929
	2 7 S 7	,	83,5 T		25 1 25 1 27 1 25 1		2 H S 7	2 E 7 E 7	***	よ 記 1 2 1 3 1 3 1 3 1 3 1 1 3 1 1 3 1 1 3 1 3	930

•			_								M	IE	EL	.T	-1	N)E	EX	(.						•				
		<u>.</u> .		1,4			<u></u>			٠. ن				·	1,0		·	0,0			0.8	T	7,0			0,6	T	_ ;0) i	
	L.	t in a	ľ			, <u>a</u>	, E	118	3]	2 7	\ <u>\texts</u>	18	7	42 119,0	£ 152	साह्य १	1,011	113,8	RISE T	42 119,8 10,8	44 114,2	120,	RIGE T	RISE T	4.2 120	£ iii	RING 12 12 12	RISE	RISE T	945
	118,0 4,2	1124 44	1 10 10	E T RIS	HIS	2 118.7 4.2	a Happing	SE T RUS	H H		2 119,4	i iig		136 1	114.2	TSE T RI		114,0	TE T	12 THE	4,4 115,0	å	115.5 12.5 CA	콅		116.0	iğ r	WISE T	RTSE 7	946
	T RISE T	1	Ē	113,6 4,4 114,3 T KTSE T	RTSE	<u>इ</u> →	113.8 4.4 114.6	119,9 4,2 120,1	E T RISE T	T RIBE 7		2	RTSE T	12 12 13 14 15 15 15 15 15 15 15 15 15 15 15 15 15	44 115,0 44 115,7	H HISE T	SE T KISE 7	12		2 7	15 7 15 RN	121.6 C	7 <u>2</u>	7 RTSE	1 THE CA	118,7 A.J.	1 22	KIDE T KIDE	THINGE	947 948
i	4.2 120,3 4,2	14.7 4.4	4,2 120,6	4.4 115,0 4.4 RTSE T RTSE	AND I	MISE T RISE	44, 115,4 4,4	12 121,2 42	THE T RIS	T RTS	12 121.7 AUS	3 44 116,1 4	al.	e a	7 44 1185 4	AUSE 7	RISE T RI	12 4,4 116,0 4	AUSE T R	RISETR	110.6 4.4 117.3 4.4 1	72.7 4.2 123.4	17.0 4.4 117.8	٦ إ	T RISE 7	118,3	12 121	118,0 4.4 118,0 118,0 7 118,0	RIBE T	8 949
	RISE T	₹	4.2	115,7 4A 116,5	THE REPORT OF	T RISE	Han A	2	T RISE T	E T RISE T	E T RISE T	115,8 4,4 117	E T RISE T	E T RISE T RISE T	117.2	1 1	7	117		DE T RISE T	E T RIS	7 PHS	18,5	RISE T RISE	T RING	\$.∄	12.		7 8	950 951
	T RISS	KISE T RISE	97Z)	1 2	T KIDE T RISE	T RISE T RISE	RISE T RIS	42 1215 4,2	117,2 44 197,8 44	연락	KISE T AII	4 118	10 44 124.24 A	ET RISE T RISE	さっ	18	-1	4 i	i i		13817	124,8 4,2 125,5	佳.	損	T RISE T	F 3	4.2 1265	2 12	T MINE T	_
1	T RINGE	T RISE T	121	1 2		T I	T RIS	124,1		T RIGHT	R	≂ ~	416		• -			1 119.7 4.4 1	2 (21) 42 1	TOE T RISE	KITSE T KITSE	42 1282 42	120,6 4,6	12 128,7 42	7 2 2	a T	42 1212 42		ACC ACC	-
	T RISE T RISE		HISE HISE	: [. :	12 120 12 12	RISE T: RISE	RISE T RI	8 4.2 125.4 4.2	1182 44 1180 44	125,1 4,2 125,8 4,2 T RISE T RISE	RTSE T RI		5,5 4,2 125,2	RISE T R	RIGETR	m,0 4,2 128,6	T RISE T D	T RISE T	24, 4,2 127,0	7 RISE 7	L MEEL HEEL L MEEL	T RISE T	17 KISE 7	12 127,9	E T RISE T	138	TE TE	122 44	954 955	_
記さな		-1	RTSE	* ñ	10		7 RISE		120		T KIE	ĝ	\$	2 €	TT S	2 42		7	42 120 42 1	2 Eg 2	NISE T RISE T R	RIBE T. RISE	RISE T RISE	12 128,0	14 120 th	RTSE T	は開	3 -	၂၂	-1
42 1241 42	2 8	a c	ATTES T	RTSE T	\$2 12E	2 8	ag i	RISE T R	1,0 4,4 121,5	127,0 4,2 127,5 4,2	T RISE T R	T RISE T R	17.4 4.2 127.9	12:7 44 123 44 1	T RISE T	27,6 4.2 128.3	122 44 127				# E	7 1	開	129,1 4,2 129,7	123,5 4,4 124,1	٦	T RISE	12,0	57 95	
128.7		127,0 4.2 12,0 4.2	Ringe	12 7 12 A	127,3 4.2	127	T RTSE	RISE	22.1	12		RISE	22	1 2 2	TISE T RISE	42 1289 42	7 (22) W	RISE T RISE	42 120 42 12 120 42	44 127	t a	1 33 T	A RSIN	42	14 124,5	RIDE T RIDE	Tige Figure	-	959	1
	1 13	ਸ ਲੋ	<u> </u>	11 T	<u> </u>	ម្ចី	7 1		122	128	រុទ្ធ	-1	ğ -	į	-	1 1	ğ		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1 <u>2</u>	7 2			5	귀	-1	SE 7	960	

•	Ū	
	Z	2
	<u> </u>	

		ME	ELT-IN	NDEX			·.								
1,5	1,3	1,2	1,0	0,9	0,7	0,6	0,5								
A REE				t mg t mg t											
	12 7 8 7 12 7 13 7 13 7 13 7 13 7 13 7 13 7 13														
42 103 103 103 103	107.4 17.2 109.5 17 117.2 17.5 17.5 17.5 17.5 17.5 17.5 17.5 17.5														
な 調 な 習	THE														
は調ま開	RTSE T RT														
12 1 2 1 2 1 2 1 2 1 2 2 1 2 2 1 2 2 1 2 2 2 1 2	E T RISE														
18 7 E 7	19 19 19 19 1		934 RRSE T 44 155,1 172 110,8												
RISE T 4,4 102,1 RISE T 4,2 107,7			た 調 な 調 な 調		で で で で で で で で で で で で で で で で で で で	2 mg 2 mg	お聞き買め								
t 麗 t 麗		t i t i i i i i i i i i i i i i i i i i		이 기는 기는 기는	調な調な調	は調は調	" 								
100,2 T RT RE 12,2 T A 12,2 T RT RE 12,2 T A 12,2 T RT RE	T RISE T	T RTSE 110,2 42 T RTSE 104,2 4,4 T RTSE 109,6 4,4		2 111,4 12 1110E 2 111,4 12 1110E 2 111,4 12 1110E 2 111,6 110E		でまっ	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1								
題ります	三世 第一章 一章 一章	東山路山荒山	18 7 H 18 -		丁麗丁麗丁		937 first r 44 1003 first r								
MRE T 4,6 1642 MRE T .4,2 110,9	1 2818 4.4 1020 1 1211 1 2511 1 2511 1 2511 1 2511 1 2511 1 2511 1 2511	KITEE T 4,2 112,2 KITEE T 4,6 113,2 KITEE T 4,2 111,0		42 1135 42 1135 42 1135 43 1074 42 1130		\$ m & m	938 mee r 44 103 mee r								
な麗な麗		た 調 な 調 な 調	t 開 t 照 c 麗	t g t g t g t	記れる	は 開ま開	t iii t iii t								
100,2 FRIESE 111,5 FRIESE 4,2	T RISE T RISE T RISE T RISE T RISE T RISE T RISE T RISE T RISE	T RTSE 113,2 4,2 T RTSE 107,2 4,4 T RTSE 17 RTSE 112,8 4,2	100,0 4,4 1 7 RTSE 113,0 4,2 1 RTSE 107,8 4,4	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	114,5 4.2 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3										
<u> </u>	# # # # # # # # # # # # # # # # # # #	; 그용 그릇 그	第一章 「最一	1를 기를 기를 기를	コラコラコ	를 거를 거									
44 1941 RISE T 113,7	HISE T 42 114,4 109,7 118,5 T 14,4 109,4 114,0 114,0 114,0 114,0 114,0 114,0 114,0			#15E T 42 1183 #15E T 44 1183 42 1168	RISE T 4,4 111,2 RISE T 4,2 118,0		941 RISE T 44 1122 RISE T								
記記された。	4.2 4.3 AUSE HUSE HUSE 4.2 4.2	t 麗 t 麗 t 麗		L MIN L MIN L	RING C RING	お記れる	1 m 2 m 9								
109,0 4,4 109,0 4,4 1 RTBE 114,4 4,2	6 3 6 3 6 3 6 3	会司会司 表司	110,8 4,4 1 T RTES 110,4 4,2 1 T RTES 110,4 4,2 1		777	. 2 . 2	. 20 . 20								
11 7 10 7 10 10 10 10 10 10 10 10 10 10 10 10 10	2 T M	1106 1106 1106 1106 1106 1106 1106 1106	HEE T II.7 4		1100	2 110,4 2 110,4 2 110,4	943 RE 1140 RE 1700								
1702 T RISE 44 110,7 4.4 1702 T RISE 4,2 110,3 4,2	MEE T 44 1114 678 T 42 117,0 178 T 44 111,1 178 T 44 111,1	なる はい		100 100 100 100 100 100 100 100 100 100	4,6 113, 4,6 113, 4,2 110, 4,2 110,	T SUBST	944 7 145 146 147 148 148 148 148 148 148 148 148 148 148								
THE T RISE TO THE TOTAL THE	T (MES T MES T 1100 A 1114 44 1122 T MES T MES T 1110 42 1170 42 1170 42 1170 T MES T 1102 44 1111 44 1111 5 MES T	ET MISE T RISE T 2 110,0 42 117,7 42 118,6 ET MISE T RISE T 5 110,0 44 111,8 44 112,8 ET MISE T RISE T 110,5 42 117,7 42 118,2	1136 T KISE T (125 44 1134 1134 1135 T KISE T A4 1134 44 1134	124 1124 44 1134 44 1142 125 1101 42 1104 42 1106 126 1107 42 1107 42 1106 127 (115E T RISE T	THE T RIBE T RIBE T 44 113.0 44 113.0 44 114.7 THE T RIBE T RIBE T 42 110.0 42 110.4 42 120.3 THE T RIBE T RIBE T	RISE T 3 44 115,1 RISE T 9 4,2 120,8	2 2 2 2 2								
2 3 2 3	इन्हेन्डन	E 1 2 1 2 1	를 기통기를 기	<u> </u>	न हुन हुन	불기를기	5 15 15								

	ζ	_	J
	Ē	Ī	7
	ć	7	5
	_	_	j
1	-	<	

		-	_	_			·			_	·		M	E	EL	.7	-	11	V	Ď	E	×	(•								ļ !
		11,0			9,9			,8 9			8,0			7,2				יע עי		• •	5,9			5,3			4,8			4,3		Ė	3,9		.
	4,2 89,2	1 88	HISE T	4,2 90,0	£ 2	KISE T	12 BB	1 23	rise T	4,2 91,6	1 200	KISE T	4:2 82.3	1 80	RISE	12 8	RISE	1		Z Z	2	RISE	t.	A SE	RISE. 1	£.	i i	RISE	2	2	RISE	12	1 20	RTSE	930
	42 80A 42	11-	8	1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	8	32	ធ គ ខ -	1/2	Ħ	î,	\$	쥝	£ 2	\$	줥	ŝ	∄ :	١,	3	100	2		t i	2	NE SE	î,	1 5	RTSE	22	1	HTSE	t g	2 1		0 .931
	4.2 B1,8 4,2	2	HISE T	t i	*	RIESE T RIESE	t ĝ	\$189 . T	HISE T	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	\$	RISE 7	42 94.7 HISE	67,9 4,4 BB,D	RTSE T	42 42 84 42		nion -	42 96,1	RTSE T	3 4,4 90,5	RISE	2	\$	2		1 27 44 87,0	31	2		3	42 848 T	1 2		1 932
	2 027 RTSE		•			7 7 70 7	KISE TERIS	44 08,0 44	RISE T HIS	12 850 KISE	*	TISE TIME	ASE T ATSE	4,4 80,2 4,	KTSE T KT	4,2 00,5 4,2	7 2	XISE TO RE	42 872 4	N 1 3513	90,5 4,4 91,8 4,4 9	THE PARTY OF	4.2 99.5 H	18	KISE T	9	ag	7		£ 83	H Belly	100 C	2 22	RISE	933
		\$2	1		2		A AN	20.7	HISE I		g £		B 7	2	긜	43	1 2	3	2	7	27		3	2	KISE T RISE	KISE T KIS	3. 2.	RTSE T KISE		E	RIDE T RIDE	<u> </u>			720
13,0	T RISE T	1.4 B)	į t	***	4	7 97 42 975 1 975	T HOSE T	30,8 4,4 PT,E		T RISE T	81 A B.18	THE TANK		2	7	<u>و</u> د	2 2	7	2	7	2 2		<u> </u>	8	7 8	3	2		RISE	8		RINGE	98,0	ျပ	035
4 of 1	HIER T	4.4 91.3	12 81,7	RE	<u> </u>	1 2 935	٦	4.4 62.6		RIDE T	44 837	41,	. 3	4.4 84.4	THE T	E T RISE T RISE	1 44 862	RISE T	0,4 4,2 101,5		AISE T	12 13	T RISE T	85.5 4.4 95.0		T RISE T	86.3 4.4 97	1 KINE 1 100.0	: 3	44		T RISE T	97,0 4,4 88,7	18	-
17.0	7		1,2 98,7 4,2	***	2 -		4	44		तह्य 🕇 साड	4 037 44 947 44 B	\$2 in 0	RISE T RIT	28.4	1 20 4	RISE T RISE	4,4 95,2 4	H A BSLN	4,2 102,5 4	7 200 7	RISE T R	1022 42 1022 42	साइट ७ साइट	4.4 97,8	i i	9	4	i ž	1	8 -	i E	HISE T	KJSE T	938	-
	100	E 2	•	T R	RITE	100g 4.2	T RTEE	6 A	i c	7	RISE 44	1820 42	E T' RISE T' RISE	1 2			77.1	7	1 to 2		T RISE	1,2 104,2 4,2	THE THE	4 98.6 4.4	2 104.0 42	RISE T RIS	1 20 1 King	12 18.8 th	KISE T KI	** 100.0 4.4	42 1043 42		#15E 7 RTS	39	_
89,9 4,2 100,6	T RISE T	E RING	2	T RIDE TO	THE STREET	ಭ	T RIES T	T RIGE T	記念論	T RIBE T	PED AL COR	100,0 4,2 15	T RISE T RISE	WISE 1	10,7	T RITE	88,1 4,4	7	2 2		T Rig	185,1 4.2	71 . 20 .	SE TRIES	12	7	TO THIS	ig S	7 M	RIE	19/2	7 3		6	→
42 101,7 42		HIEE T	4,2 102,5	1 See	TI SEE	42 (B)	7 2	RISE T	4,2 104,0	7 3	. 7	ΙĒ	715	7	12 1855 1505	KIBE T	24.		105.3 4.2 104.7 R	100 Te	T. RISE T	06,1 4.2 107,		I BERN	100,8 4,2 107		T RISE T	Ĉ	T RING T	: 2	22		1	941 942	
2 1020 42	22 7 87.0 4.4 1 87.0 4.4	RISE T RISE	ĝ.	1 2 2	7	104,2	1 20	4	Di,o	ANDER TO RESE	RISE T RISE	4,2 105,7	기[편	7	42 108/4	T RISE T RISE		1 101	ទ ដ	1	a	4.2 107,0	T RESE T	7	107,7 4,2 108,6	RIESE TO DIESE	FRIED.	C 123	RISE T	HEELT	ŝ	T RIGE T	3311	943	4
100,5 4,2	1 2 2	T Rings	10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	8	T' RISE	105,0 Kish	2 2	T RISE	2 105,8 4.2		35 T 815E	2 108,6 4,2	7, 000 7,	THE P RISE	2 107,3 4,2	T RINGE	A SHEET MAN		THE T RISE	北 前 記	٦,	3 -		133	42 100,4 4,2		RISE T RISE	ਛੋ	4,4 104,5 RTSE T	RTSE T	4.2 tigg	1 25	RISE T	944	
Ç L	1 <u>8</u>	4	<u> </u>	88	4	3	į	-1	ē.	1 8	7	ğ .	1 2	7	108,1	-	3 -	108,6	7	. 103,2	7	7 42 100 F	Ē	-i SS	r ž	100			2 18		e e		RISE T	945	ŀ

				MEL	T-IN	DEX					
4,0	3,6	3,2	2,9	2,6	2,3	·2,1	1,9	1,7	1,5	1,4	·.
4.2 g	AT SE	T HERE		t Right	12 HISE C	A12 1	ALSE HUSE	AT SERVICE	ATTSE ATTSE	### ##################################	930
				2 1 G 7							Ö
	4.4 62.7 RISE T 4.2 99,3		は	HTSE T 4,4 94,7 HTSE T 4,2 100,3	1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	135 T	KITSE T 4,4 00,5 KITSE T 4,2 102,1		HISE T 4,4 97,7 HISE T 4,2 101,3	1, 100,0 1,	931
t Right	お聞き関	1 2 2 E	お調よ調	開土層の	お麗と麗	ATIBE	ALA ALA ALA	ATTE	A RINGE	6 A138	-
		夏っとっ	8 - 8 -	를 가 를 가 소 기 소 기	हैं न है न • य • य	18,7 T	18 T 8 T	商 7 8 7	E 28 - 28	ğ 7 8 7	932
C'es C'r	1- 1-	RTSE T 4,4 85,7 RTSE T 4,2 101,3	#15E T #4.4 08.3 #15E T #2. 101.9	RTSE T : 4.4 97,0 RTSE T : 4.2 102,8		RISE T 4,4 98,2 RISE T 4,2 103,6	RISE T 4,4 89,7 RISE T 4,2 104,4	RISE T 4,4 90,3 RISE T 4,2 104,8	KISE T 4,4 80,9 KISE T 4,2 105,6	RISE T 4.4 100,3 RISE T 4.2 105,0	933
企業企業	お麗な麗	お類な類	お記れ	点点点	お記れる	A RISE	A RITES	90,3 4,4 17 KISE 104,0 4,2	12 E E	T RISE 100,3 4,4 T RISE 105,0 4,2	—
10,0 T A1 S	13 13	12 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	8 - 2 -	10,7 T RISE 14, 12, RISE 14, RISE	E 18 1		夏中夏 丁	第十章 マ	로 기를 기	혈기로기	934
4.4 96.4 RTSE T 4.2 102.0	1, 1931 1, 1931 1, 1931 1, 1931 1, 1931			RISE T 4.2 104.8	RTSE T 4,4 99,9 RTSE T 4,2 105,5	RISE T 4,4 100,4 RISE T: 4,2 100,0	RISE T 4,4 100,9 RISE T 4,2 108,5	4.4 101,5 RTSE T 4.2 107,1		RISE T 4,4 102,5 RISE T 4,2 108,1	gg gg
\$ 2 g 2	t i i t i	お照な問	1 H 2 H	原 お願る		£ 3 € 3	RITSE			12 13 13 13 14 15 15 15 15 15 15 15 15 15 15 15 15 15	 1
102,1 42.	夏日恩日	중기용기	8 7 8 n	101,2 4,4 103,6 4,2	1 g 7 g 7	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		夏一夏一	調ける。	혈기월기	936
4.4 98.5 RTSE T	I	## ## ### ### ### ####################	ATSE T 4,4 100,6 ATSE T 4,2 106,2	4,4 101,2 RTSE T 4,2 106,8	RTSE T 4.4 101,9 RTSE T 4.2 107,8			RISE T 4,4 103,6 RISE T 4,2 100,2		お話	937
2 m 2 m	1.2 R 2.2	t ag t			2 8 4 8 2 8 4		RIES		T RTBE 104.2 4.6 T RTBE 109.8 4.2	104,5 4,4 104,5 4,4 17 87,852 110,1 4,2:	┝┷┥
	1		\$ 7 \$ 7 \$ 8 8 8	第一章 マ	買っ魔っ	夏日夏日	ig a ig a	103,8 110,2	ラマ 原子	## 1 EE 1	938
4,4 100,5 HISE T 4,2 106,1	1012 1012 1013 1013 1013 1013 1013 1013	Mise T 4,4 101,0 Rise T 4,2 107,5		#15E T 4,4 103,2 175E T 4,2 108,6	ATSE T 4.2 100,5 4.2 100,5	RISE T 4.4 104,4 RISE T 4.2 110.0		44 10 10 11 11 11 11 11 11 11 11 11 11 11 11 1		RTSE 11	939
1 H 2 H	1 2 E	101,0 4,4 107,8 4,2 107,8 4,2		2 m 2 m	12 AUST	RTSE AU 4.2	T RISE 106,0 4,4 T RISE 110,0 3,2	105,0 4,4 105,0 4,4 11 RTSE 111,2 4,2	T RISE T	106,5 4,4 106,5 4,4 17 RTSE 112,1 4,2	
<u> </u>	第二章 7	夏一夏一	夏山夏山	日間に関す	즐거롱ㅋ	불 기룡 기	まっぽっ	12 구 6 구	12 7 13 7	19 T	940
King T	"I "'I "		AA 104,4 RISE T 42 110,0	RISE T 4,4 105,1 RISE T 4,2 110,7	KITSE 1	12 13 15 15 15 15 15 15 15 15 15 15 15 15 15			112	ATISE T	941
t in t				10,7 T RISE 10,7 T RISE 10,7 T RISE 10,7 T RISE	T RISE 105,9 4,4 T RISE 111,4 4,2		100,9 4,4 100,9 4,4 11 Kilber 112,6 4,2	T RISE 107,4 4,4 T RISE 113,1 4,2		100,4 100,4 114,0 114,0 114,0 114,0	
夏一夏一	夏コミコ	ラマミュ	를 기를 기	를 기를 기	ディスティ	를 구를 구	1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	13 T 18 T	1160 T	942
1036 L		4.4 10 8.752 11	2 8 2 8	E # E 3	t Right Right	13 A RE			お聞せ聞	44 H	943
12 T 42 T		103,0 4,4 103,0 4,4 103,2 4,2	1632 44 1632 44 17 Rifee 111,0 4,3	T RTEE 1030 4.4 T RTEE 1129 4.3	T RISE 107,9 4,4 T RISE 110,2 4,2	113,7 4.2 113,7 4.2	1027 4.4 1027 4.4 11 1018E	100,2 4,4 100,2 4,4 17 177822 114,0 4,2	16,0 4,2 16,0 4,2 16,0 4,2 16,0 4,2		
· 露 · 。	まっぽっ	ラマ 調 コ	· 第一類	更可見一	部 7 8 1回5 8 7 2 1141	SE T 4 109,0 2 114,0					944
12 R				は調味調	RINGE 1,2	A RISE	ta Right	ta Range	おっぱい	お調ま調	_
豊一麗 マ	हुँ न हुँ न	で 調り	를 기를 기	1 3 下	でいる。	를 기용 기	등 기를 기	를 기를 기	중기를 기	뚫겨를 게	945

_							-		IV		I L	- 1	<u>-</u>	1	IL)E	->								•		l
	5.		-1 4		 3		ĺ	<u>-</u>		<u>-</u>	• .		1,0			0,9		- 4	0.8		0.7		0,6	T.	_)	٠.
42 1033 42 1044 42 1056 42 1067 43 107] 42 1056 42 1066 42 1166 42 1115 42 1126 42	HISE T RISE T RI	4 42 103,0 42 104,8 42 105,0 42 107,0 42 108,1 42 108,1 42 110,1 42 110,1 42 117,0 42 117,0 43 117,0 4	HE THE T RISE T	42 104.0 42 108.1 42 109.2 42 107.2 42 108.4 42 108.5 42 110.5 42 1115 17 1175 T RISE T	4.4 67.2 . 4.4 69.3 4.4 69.5 4.4 100.5 4.4 101.7 4.4 102.5 4.4 103	RIDE T RI	ANDE T RISE T RI	4.4 91.5 44 98.7 44 98.9 4.4 101.0 4.4 102.1 4.4 102.2 14.4 102.2	0.5 4.2 104.7 4.2 105.0 4.2 107.0 4.2 105.1 4.2 105.1 4.2 105.2 4.2 117.2 4.2 117.2 4.7 117.2 T RISE	78 44 00.1 44 101.2 44 101.4 44 102.5 44 105.5 44 106.5 44 106.5 44 106.5 44 107.5 44 108.5 1	HEEF RISE T RISE	NO. 42 105,1 42 105,2 43 107,4 42 109,5 42 109,5 42 109,5 42 110,6 42 111,7 43 112,5 44	83 44 88 44 100 44 101 44 102 44 103	T - RISE T RISE	14.2 105.6 4.2 105.6 4.2 107.6 107.6	44 997 44 999 44 10101 44 1022 44 1033 44 1034 44 1034 44 1034 44 1034 44 1034 44 1034 144 1034 134 134 134 134 134 134 134 134 134 1	RISE T RI	HTSE T HT	44 68.1 44 100.3 44 101.5 44 102.5 44 107.7 44 107.5 47 1	4.2 105.2 4.2 109.4 4.2 109.5 4.2 109.6 4.2 110.6 4.2 111.6 4.2 111.6 4.3 112.6 4.3 11	4.4 69.5 4.4 101.6 1.4 103.6 103.6 1	4.2 105.7 4.2 105.9 4.2 105.0 4.2 105.1 4.2 105.2 4.2 111.3 4.2 111.3 4.2 112.4 4.2 112.4 4.2 113.4 4.2 11	44 100,1 44 101,2 44, 102,4 44 104,6 44 100,7 44 100,8 44 107,8 44 100,8 44 107,8 44	108.3 4.2 107.4 4.2 109.5 4.2 109.7 4.2 110.6 4.2 111.5 4.2 112.6 4.2 113.0 4.2 113.0 4.2 113.6 4.2 118.6	TISE T RISE T RI	RIDE T RISE T RI	027 020 020
	- 11			110	!	N	19	18	ᆌ	7		1 2	7	-	ä	٠,	3	11. 12.	1 g	1 🗒	1 8	1 5	구	7		945	

·		·		MEL	T-IN	DEX	(
30,0	27,0	24,0	22,0	20,0	18,0	16,0	14,0	13,0	12,0	11,0	·.
B 18 C	4.4 59 13 64 14 59 17 69	RTSE 1	42 E BERN	414 EE 142 EE 14	ALA S	RTSE 1	HISE 4,4 0	4.4 R	RTISE C	AJA:	9
				86 T 55 T							5
	44	は 2 日本 日	\$ 7 \$ 7 \$ 2 \$ \$	14.4 eq.6 14.2 eq.6 14.2 eq.2	2 T 2 T		4.4 B				916
		は調味調		A REST	A RINGE	RITSE RITSE	T HISE	9 44 44 12 12	1 KIRE 1 44 A 4	رة الله الله الله الله الله الله الله الل	9
2 - 8 -	윤기운기	뚫겨울ㅋ	을 가운 게	97 T 25 T	7 RISE 02,8 4,4 17 RISE 03,4 4,2	2 7 E 7	경기없기	F 78 -		7 7 8 7	17
		TO THE RESERVE		RISE 1	A SE THE	4.4. A SELVA	和麗			RTISE RTISE	91
01,1 4,4 17 RTING 4,2		はいませる。	1 818 T 818 T 828	CALL ATTE	T RISE 64,2 4,4 17 RISE 60,8 4,2	T RTSE 65.0 4.4 T RTSE 70.7 4.2	2 1 8 7 2 2 2 3	T RTSE 50,5 4,4 T RTSE 72,1 4,2	17 Kise 17 Kise 17 Aise 12,7 4,2	2 1 3 1	8
2 - B			를 가운 기	2 H 2 H	2 日本 日	SE T 4 89,5 SE T 2 72,1			RTSE T 44 684 RTSE T 42 742	RTSE T 44 89,2 RTSE T 42 74,8	919
		お聞き聞	お聞き聞	12 H 2 H 32 H 32 H 32 H 32 H 32 H 32 H 3	T RISE T RISE T A12	な調な調	AT A RES	お聞き間	2 g 2 g	ま 記 は 記 記 は 記 は 記 は 記 は 記 は 記 は 記 は 記 は	_
	걸그용그	불구용구	\$ 1 B 1	경기용기	12 1 2 1	경기왕기			경기경기	7 7 7 7 25 7 25 7 25 7 25 7 25 7 25 7 2	920
4.4 65,3 RISE 7 4.2 70,9				RISE T 44 67,8 RISE T 42 734		RITSE 1	44 7 42 7 42 7	ANSE 7	RITSE 42 7	KITSE A.A. 1 KITSE 12 7	921
ta Militar		1	お記れる	17 472 3213 1 3213 1 1 473 3213 1	T RISE 68,5 4,4 T RISE 74,1 4,2	1° RISE 84,3 4,4 1° RISE 74,9 4,2	7 RISE 70,2 4,4 T RISE 73,9 4,2	70,8 4,4 170,8 4,4 17 RTSE 70,4 4,2	T RISE T1.4 4.4 T1.6 RISE T1.0 4.2	T 4.5 17.5 T 1.5 17.5	_
2 -18 -	2 - 8 -			E 7 74,8	75 T 85 T	# 70,7 # 70,7 # 70,5	報 7 4 7以 報 7 2 72	2 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		2 E Z T Z T	922
HISE		2 mg & mg	お聞き間	な調な調		RISE 45	2 mg 2 mg	42 R	ATTE		
를 기울 -	₹ 7 g. 7	選っ盟ュ	麗コミコ	きょり きょ	72 7 73 7	2 - 2 -	日間に関す	로그룹그	ह्य न हुन	8 - 8 -	923
12 H				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	£ m € m	お聞き聞			1 m 2 m	12 mg 2 mg	924
75 7 KISE	700 T RING	7 1,7 1,7 1,7 1,7 1,7 1,7 1,7 1,7 1,7 1,	71.2 4.4 71.3 4.4 71.8 4.2	경기경기	2727	हुन हून	경기본기	8 7 6 7	급기호기	3 4 2 4	
2 H 2 T		2 T 2 T		A14 73.2 A115E T A12 74.0	RISE T 4,4 73,9 RISE T 4,2 79,5				RISE 1		925
		ta mag	12.5 4.4 17.8 4.4 17. RISE 18.2 4.2	12 H	ANSE ANSE	HISE HISE	L RIES	A A A	7 RISE 70,6 4,4 7 RISE 82,4 4,2	E T T T	
경구경구	경기경기	경기관기	神山路 上	무기중기	문기원기	흥구흥구	日 当 日 日				926
t ng t		SEL SEL	SE SE SE		お題を調	ATSE ATSE ATSE	な器を習	調金調の		電子質な	
		2 7 5 7			B - 2 -	윤기군기	문가전기	加工部に	第一号 コ		927
4,4 74,5 4,2 74,5 4,2 13,1			***				HIEE T	A2 C3.0	· · · · · · · · · · · · · · · · · · ·	43. G	928
2 11 2 11				e e e e e e e e e e e e e e e e e e e	A A A A A A A A A A A A A A A A A A A		42 63 63			<u> </u>	
물 거리.ㅋ	最一度コ	E 7 2 7	27.0 12.2	では、1	1 2 4	日日日	B 7 B 7				929
お習な習	お聞き聞	1 ag 1 ag	2 R 2 R	1 mg 1 mg	お記れる	# # R R R R R R R R R R R R R R R R R R	A RESE	おいまま	お記念器		
유구출구	즐거움거	アポト器	第十四十	음그출그	四十四十	の 場下器 コ		F 23 T		B - B -	88

D
Ш
S
习
~

	_				_								V	1E	ΞL	_7	Γ-	11	V	D	E	X											
		11,0			9,9			œ, 9,			8,0			``		T	Ç				л 0	T			4,8		T	4,3			 လ ဝ.	†	•
. H. 187 12 15 15 15 15 15 15 15 15 15 15 15 15 15	HIGH T HIGH	44 64.8 44 68.2 44 67.7 44 68.2 44 70.0 44 72.0 44 72.1 14 72.7 17.7 17.7	HIGH T RISE TO THE TOTAL A2 76,0 42 77,0 42 78,4 42 78,8 42 81,1 42 82,5 42	HISE T RISE T RI	44 64 44 650 44 67,1 44 685 44 689 44 714 47 TO THE T RISE T RISE T RISE T RISE	HISE T 8755 T Gree T 42 763 42 778 42 782 42 805 42 819 42 82 42	ATTER T KINSE T	44 . 648 44 678 44 693 44 707 44 721 44 738 44 76 77 RISE T	RIBE T RISE T RISE T RISE T RISE T RISE	3 42 728 42 742 42 757 42 77 RISE T RISE T RISE T RISE T	TIBE T TYPE T THE THE THE THE THE THE THE THE THE	HISE T HISE T HISE T HISE T HISE T HISE T HISE	42 721 42 755 42 755 43 784 42 786 7 RISE T RISE T RISE T RISE	1,2 TO 000 44 01.9 44 00.4 44 70.9 44 70.3 44 70.1 44 70.5 44 70.8 44 70.2	HISE T	42 728 42 743 42 757 42 772 42 776 42 800 42 814 42 878 42 879 42 879	C1. RIGHT T RIGHT RIGHT T RIGH	THE THISE	42 705 42 750 42 704 42 779 42 779 42 807 42 821 42 825 42 840 42	HISE T RISE T RI	FO 44 609 44 603 44 709 17 709	42 742 42 767 42 772 42 788 42 801 42 815 42 829 42 843 42 86 42	RTSE T RT	RIBE T RISE T RI	42 749 42 784 42 770 17 THE T RISE T	44 60.3 44 70.8 14 70.2 44 70.7 44 76.1 44 76.6 1 7	.TG.7 42 77.1 42 78.0 42 80.1 42 81.5 42 82.9 42 84.3 4.2 85.7 42 87.0 4.2	HISSE T HISSE T TOTAL TO 44 744 44 759 44 773 44 787 44 614 44 628	T RIBE T RISE T	HISE T	THISE T RISE T	1-	010 012
0,0 42 843 42	T RISE T RISE	RISE T RISE	ELA 42 ELA 42	72 .44 TP. 44	7	2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	78,9 4,4 80,2 4,4	T RISE T RISE	85,3 4,2 89,6 4,2	T RISE T RISE	TE RISE T RISE	88,1 4,2 57,	T RISE T	RISE T	13 18	RISE T RISE T RISE	2	1	7 7	4 819 44 832 4	E 7 RISE 7 RISE 7 RISE 7	RISE T RISE T RI	P.7	89,0 4,2 90,2	HISE T MISE TO	T RISE T	T RISE T		90,4 4,2 91,6	4,4 84,7 4,4 86,0	1 300 TO	925 926	
85,0 4,2 85,8 4,2 88,0	1 KISE T RISE T	T RISE T RISE T RISE	RISE T RISE T	0.7 4.4 82.0 4.4	T RISE T RISE	T RISE T RISE	H.5 44 827 44	ा साइट र साइ	67.8 4.2 Eq.1 4.2 80.4 4.2	1 2 2 2	} ~	88.7 A	7 8	를 기	84	E T RISE T RISE T RISE	- ×	+	- T	5	12 22 12	RISE T RISE	RISE T RISE T	91.5 4.2 82.8 4.3	1 4 B1 4	1 2	RINGE	T KISE T RISE		87,2 4.4 89,5	76 976 17	330	
		4 8 8	***	84.4	805	7	85 25	7 7	2 4	85,0	7	15 - C	2 88,7	186 1	12 81	TE STA	T HE	12 B)8	TISE T		12 86	1 E	RISE T	おいま	4,4 89,6	1 8	2 12	ALC:	RTSE	AL ON O	930	-	

	· .	• • •	MEL	T-IN	DEX	(}	.
4,0	.3,6	3,2	2,6	2,3	2,1	1,9	1,7	1,5	1,4	••
	1 1	4.2 Rise 4.2 4.2								9
		3.72727 2.727								5
12 77.8 12 77.8	#102 T. T. T. C. 17 C. 1	RTSE T 4,2 74,7 RTSE T 4,4 73,6 RTSE T 4,2 79,1	4,4 7,4 RISE 1 4,2 80 RISE 1 4,2 80 RISE 1 4,4 7,4		RISE 7	おかれる		1 章 麗 4		91
77,8 4.2			74,7 4,4 17 1888 14 1,2; 14 1,4; 14 1,4; 14 1,4; 15 1,6; 16 1,6; 17 1,6; 17 1,6; 18 1,		78,0 4,4 78,0 4,4 7 RISE 81,9 4,2	A RISE		1 7 1 B		
결구절구	경기라기	불 기를 기르기	第十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二	で 報 と 器	日本では	문기를기	음 기절 기울 -	12 7 2	그렇그	917
4,4 74,9 RISE T 4,2 80,8	HISE 75.0	HISE T 16,4 17, 12, 12, 12, 12, 12, 12, 12, 12, 12, 12	MISE T 44 77,8 MISE T 4,2 83,3 RISE T 4,4 77,0	RISE T 44 703 RISE T 42 840	RTSE 7	12 ET		THE REAL PROPERTY.	,	918
		T RTSE 62,6 4,2 T RTSE 17 RTSE 17 RTSE 14,4 4,4 4,4 4,4 4,4 4,4 4,4 4,4 4,4 4,			75, RTSS 78, 44, RTSS 4,5, 4,2	79,4 17 RTSE 42.4 4.4 4.4 4.4 4.4 4.4 4.4 4.4 4.4 4.	2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1	1	7 99 7 RTSE	9
를 가를 구	日本語	문구불구통구	불 기본 기본 기	문구불구	関するコ	를 기를 기	를 가운 가용.	12 -1 8	7 B 7	<u>3</u>
44 77.8 43 83.4		RISE T 4.2 65,4 RISE T 4.4 70,2 RISE T 4.2 84,8	4.4 17.80 T	RTSE T 4,4 81,2 RTSE T 4,2 85,8	RISE T 4% 81, RISE T 42 87,	HIRE 1	4.2 B3.1 RISE T		RITSE T	920
t 2 5	お頭よ頭	お聞き聞き	\$ 2	12 12 12 12 12 12 12 12 12 12 12 12 12 1	17 RISE 81,7 4,4 17 RISE 87,3 4,2	L Right	3 3 6 3 6 3			
2 7 22 7 2 8 8 2 8 8	끊겨謀ㅋ	272727	문기중기동기	경기장기	8 1 2 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	를 가운 가를 -	를 기울	⊣ B →	921
a wi. u	RISE T 4.4 81.2 RISE T 4.2 84.6	HISE T. 4,2 88,2 RISE T 4,4 82,0 RISE T 4,2 87,6		#15E T #15E T #15E T	RISE T 4,4 84,5 RISE T 4,2 90,1	RTSE T.	42 e1,9 RISE T 44 65,6 RISE T	t in t	HISE LA B	82
1 RIE 4.2		A RITES	A MEL LA ME	RTEE A	1 R R R	A RATE	Service of the servic			_
19 - 18 -		물 - 물 - 물 -	語り寄り居り	器中間日	S 그 를 그	월 -1 월 -1 <u>[</u>	3 - 1 3 - 1 2 -	18 -18	- 8 -	923
42 8373 42 8373 42 8373			4.4. HSUN	12 83 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	4.2 ESTA 4.2 ESTA 4.2 ESTA	1. H				924
12 mg 2 mg	2 g 2 g	ATTE	96,5 7 RTSE	90,7 4.4 17 HISE 42,3 4.2	2 RIES	な 門 は 副 は	7 4.6 4.2 TRINGS	温ヶ島 よ 温な	╼╀╾╼╂	_
8 7 g -	용가용기	물 기용 기용 기	\$ 7 B 7 3 7	S 7 8 7	三世 第四	본기르기	3 - 3 - 3 - 3	1 E 1 E	7 g 7	925
AL BEAD			RISE A	RISE ALA ALA ALA ALA ALA ALA ALA ALA ALA AL	2 g 2	た 罰 た 罰 は	は は は 記 は 記 む			926
01.5 T 82.5 T 82	2 7 8 7 2 8 2 8 3	T RISE T RISE T RISE RIA 4,4 T RISE RIA 4,4 T RISE RIA 4,2	## RTSE ## ## ## ## ## ## ## ## ## ## ## ## ##	\$ 7 8 7 \$ 3 \$ 3	\$ 7 B 7	17 RTSE 14.4 RTSE 14.0 4.2	2 7 2 7 2 7 2 7 2 7 2 7 2 7 2 7 2 7 2 7	를 다 등 다 됐다.		
E 7 2 7	B 4 8 4	2 1 2 1 2 4	2 18 18 1	2 日 2 日 2 日 2 日 2 日 2 日 2 日 3	2 H 2 T			1 2 - 2 2 1 2 - 2		927
ALC C				お記録	7 RISE 91,1 4,4 7 RISE 96,7 4,2	A REE	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			928
2 7 E 7		24 42 30 1 1 20 24 20 1 1 20 24 20 20 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		27 C T C C C C C C C C C C C C C C C C C	월 기 및 기 소리 소리	유 크 등 크 로		를 구를 1 등 기를		
1		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		ताहर T 4,4 ह्य ताहर T	MEE T 44 -834 MES T 42 842	THE THE TABLE TO THE TABLE TABLE TO THE TABLE TABLE TO THE TABLE	4.2 1000 THE T			929
	t m t m	おいません	RITSE ALA	B RITSE	2 R 4 R	は異な調は		1 m 2		-
		5 7 2 7 8 7	2 - 2 - 2 -	8 7 E 7	8 - F -	8 - 8 - 8			- 8 -	ဗ္ဗ

	r	·			.	MEL	T-IN	IDE)	<				1.
		, ,	1,4	1,3	1,2	1,1	1,0	0,9	0,8	. 0,7	0,6	0,0	
27 Pm 27 Pm 25 Pm	42 843 42 848 42 862 42 877 42 881 42 905 42 818 42 87 17 RIDE T RIDE	4.4 76.2 4.4 77.7 4.4 78.2 17 87.5E 17	TREE T RESE T RE	HIGH T RIGHT	HIGH T RISE T RI	HISE T	1,0. 44 180 1 180	0,9 4.4 78.4 4.4 78.6 78.5 78.	HISE T HI	HTSE T HT	THISE THISE THISE THE THE THE THISE	T RIGHT RIGH	15 916 917 918 919 921 921 921 921 921 922 923 9
85,9 4,2 87,2 4,2 88,4 4,2 89,7	T RISE T RISE T RISE T	00.2 4.2 07.5 4.2 98.8 4.2 100.0 T MTSE T MTSE T MTSE T 90.3 4.4 98.8 4.4 92.8 4.4 94.1	94.0 4.2 97.3 14.2 97.0 17 RTSE T RTS	26,9 4,2 99,2 4,2 99,5 4,2 T HISE T HISE T HIS 20,9 4,4 92,2 4,4 93,5 4,4	T RISE T HISE T RISE 7.3 4.2 90.6 4.2 90.8 4.2 T RISE T RISE T RISE 81.3 4.4 92.0 4.4 90.9 4.4	MISE T MISE T MISE 7 4.2 89.0 4.2 109.2 4.2 MISE T MISE T MISE 7 4.4 89.0 4.4 84.2 4.4	HISE T RISE T RIS RISE T RISE T RIS	10,5 4,2 100,8 4,2 101,1 4, 17 1715E T 1715E T 171 25 4,4 12,0 4,4 12,0 4,	SE T RISE T RISE T SE T RISE T RISE T SE T RISE T RISE T	HISE T HI	4.2 100,0 4.2 104,3 4.2 102,0 RISE T RISE T RISE T 4.4 884 4.4 881 4.4 884	925 926 927 92 RIGHT FIRST FIRST FIRST 44 644 45 65 44 65 44 65 44 65 44 65 44 65 44 65 44 65 44 65 64 64 65 64 64 65 64 64 65 64 64 65 64 64 65 64 64 65 64 64 64 65 64 64 64 64 64 64 64 64 64 64 64 64 64	
ĝ -	1 50 52	1 th 2	1 86 T NIE 1	7 RISE 101,9 4,2 17 RISE 95,0 4,4	\$ 2 m	101,5 4.2 (02,7 4.2 (03,9) 1 101,5 4.2 (02,7 4.2 (03,9) 1 101,5 4.4 (02,7 4.2 (03,9) 1 101,5 4.4 (02,7 4.2 (03,9)	10,1 · 4.2 10,1 · 4.2 17 RTSE	13E T HISE 12 - 103,6 4,2 15E T HISE 14 97,6 4,4	- A ~ A	T HISE T	RISE T RISE 4.2 105,0 4.2 RISE T RISE	929 8. 7	

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
D BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
☐ OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.